



EDUDUMP

Pass your next certification exam with our free practice resources.

- ★ Welcome to EduDump, a global hub for ambitious learners.
- ★ Use our updated question bank to reach your goals faster.
- ★ Driven by our mission to strengthen the IT world with free, high-quality content.

Select a vendor ...

OR

Exam Code Or Keyword ...

Search Exams

-  **Security & Privacy**
ActualVCE respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.
-  **365 Days Free Updates**
Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.
-  **Instant Download**
After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact *ActualVCE*.
-  **Try Before Buy**
ActualVCE offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

95%

Said the test questions were almost same

97%

Passed the exams with the material

98%

Found the study guides effective and helpful

<https://www.edudump.com/>

Leading Professional Certification Hub & Verified Exam Community Prep

Exam : 920-197

Title : BCM50 Rls.2.0 and BCM200/400
Rls.4.0 Config and Maintenance

Vendors : Nortel

Version : DEMO

NO.1 A customer with a BCM400 has a requirement of one T1, six PSTN analog lines and 12 digital

telephones. What are the minimum Media Bay Module (MBM) requirements?

- A. one DTM and one G8X16
- B. one BRIM and one GASM8
- C. one GATM8 and one G4X16
- D. one GATM4 and one DSM16+

Answer:A

NO.2 A customer is installing a GASM8 in a BCM400 in the North American region. They want to set the

module to enhanced mode. How must the Mode/Country DIP switches on the right side, at the rear of the

module, be set?

- A. Set all DIP switches to On.
- B. Set all DIP switches to Off.
- C. Set the first DIP switch to On and the rest (2-8) to Off.
- D. Set the first DIP switch to Off and the rest (2-8) to On.

Answer: C

NO.3 A technician is converting a customer's Norstar system to a BCM200/400. The customer has existing

analog E&M trunks. How can these trunks be made to work on the new system?

- A. Install a DTM.
- B. Add keycodes.
- C. Program them on a FEM.
- D. Configure them on a BRI module.

Answer: C

NO.4 A customer added new floor space to the warehouse, and had some electricians run cable to the new

area. When a T7316 set is connected, the line indicators flash continually. The set is about 1950 feet (600

meters) from the BCM. Which step can be taken to correct the problem?

- A. Use a SAPS with the T7316E.
- B. Replace the phone with a T7100.
- C. Turn the loop length option in Element Manager to "long".
- D. Advise the customer that the maximum distance is 1500 feet.

Answer:A

NO.5 A customer is preparing to install a G4X16 module in a BCM400. They want the module to automatically download firmware upgrades. The country dipswitches (the right set of switches) must be confirmed they are in the correct position. Which statement about country DIP switches is true?

- A. Ensure that all of the country DIP switches are set to Off.
- B. Ensure that all of the country DIP switches are set to On.
- C. Ensure that the first country DIP switch is set to Off and the rest are set to On.
- D. Ensure that the first two country DIP switches are set to On and the rest are set to Off.

Answer:A

NO.6 A technician is supporting BCM50 RIs. 2.0 and BCM RIs. 4.0. Business Element Manager has just been installed from the BCM50 RIs. 2.0 Administrator Applications download web page. Which steps are needed to connect to both systems?

- A. Both versions of BCM Element Manager must be installed.
- B. Add New Network Element, connect to the BCM50, and accept cartridge download.
- C. Go to the BCM50 Administrator Applications download web page and select the BCM50 MIBs.
- D. Go to Nortel's Customer Support/Software Downloads web page and select the Element Manager software update.

Answer: B

NO.7 Which Media Bay Module (MBM) can be combined with the G4x16 on the same DS30 bus on a BCM200/400?

- A. DTM
- B. GASM8
- C. GATM4
- D. BRI S/T

Answer: C

NO.8 On a company's default system, six buses of DS30 channel blocks are assigned to

Media Bay Modules

(MBMs) (2/6 channel split). The DS30 allocation needs to be changed to a 3/5 split to accommodate

increased IP telephony requirements. Which statement about how this change can be accomplished is

true?

- A. The BCM 200/400 assigns bus 6 to the voice data sector.
- B. The BCM 200/400 assigns bus 7 to the voice data sector.
- C. The BCM 200/400 assigns bus 6 to the voice data sector through the MBM dip switches.
- D. The BCM 200/400 assigns bus 7 to the voice data sector, although all telephony programming will be defaulted.

Answer: B